

VR4325XP

- Vertical Machining Center
- Table : 51" x 25.5"
- Travels : 43" x 25.5" x 23.6"
- Control : 9000



Shown with options



MILLTRONICS USA
LET'S INVENT



SPECIFICATIONS:

CAPACITY:	
Travels	43 x 25.5 x 23.6" (1100 x 650 x 600 mm)
Table Size	51 x 25.5" (1300 x 650mm)
Allowable Table Load	2500 lbs (1100 kg)
T-Slot Size	.71" (18 mm)

SPINDLE:	
Spindle Nose Line to Table Distance	5.9-29.5" (150-750 mm)
Column to Spindle Center	27.6" (700 mm)
Spindle Taper	ISO No. 50
Standard Spindle Speed	6000 RPM
Spindle transmission	Geared Head
Low range speed	10 - 265 RPM
Mid range speed	266 - 1323 RPM
High range speed	1324 - 6000 RPM
AC spindle motor (Opt)	35/25 HP (26/18 kW) Delta/WYE

AUTOMATIC TOOL CHANGER:	
Number of Tools	24 Double Arm
Tool Shank	CT50
Pull Stud	ANSI 45° Retention Knob Style CT-Flange 50 Taper
Max. Tool Diameter	4" (100 mm)
Max. Tool Length	10" (250 mm)
Max. Tool Weight	33 lbs (15 kg)

MOTION:	
XY/Z Axis Rapid Traverse Rate	800/550 IPM (20/14 m/min)
Max. Cutting Feed Rate	500 IPM (12.7 m/min)
Least Command Increment	0.0001" (0.001 mm)
Positioning Accuracy	+/- 0.0002" (+/- 0.005 mm)
Repeatability	0.0002" (+/- 0.005 mm)
Axis Thrust Force XYZ	5280/8065/8065 lbs (2395/3660/3660 kg)

GENERAL:	
Machine Height	124" (3150 mm)
Floor Space Required (W x D)	121 x 122" (3075 x 3000 mm)
Additional Width for Auger/Conveyor	29" (763 mm)
Machine Weight	17,600lbs. (8000 kg)
Power Required	48 KVA / 125 Amps
Voltage Required	208-240 Volts/3 Phase

MACHINE STANDARDS:

- Milltronics 9000 Series CNC control
- 24 pocket Arm ATC
- 6000 RPM Spindle
- Automatic Lubrication
- Chip Auger
- 35/25 HP dual speed spindle motor with geared head
- Coolant Through Spindle Ready
- 15" color LCD touch screen display
- Enclosure Wash Down
- Square Box Way Construction
- Flood coolant
- 800 IPM rapid traverse rate
- Work light
- Rigid tapping
- Single spare "M" function
- 120 GB solid state hard drive
- Solid Model Graphic Display
- DXF file import
- Full Enclosure
- Networking



9000 CNC

The new standard of control

With its conversational programming, onscreen help, intuitive menus, color graphics and prompted tool settings, the 9000 CNC helps new operators train faster and become more productive sooner. It's a window based platform runs parts programmed conversationally or tool paths generated by a CAM system.

CONTROL STANDARDS:

- Milltronics 9000 CNC includes 120 GB solid state hard drive
 - Windows® Intel i5 Dual Core processor
 - Enhanced CPU with block processing speed of 3000 bps with enhanced jerk control and look ahead
 - 15" color resistive touch screen (LED backlit) 1024 x 768 resolution, driven by a high-end 600 Mhz graphics card featuring an on-board CPU and 1 GB video memory
 - Auto DXF file import
 - 3D part and wire frame tool path graphics plus solid modeling graphics
- Conversational, G&M code or CAD/CAM programming including coordinate rotating, scaling, mirror image, thread mill, engraving, helical interpolation, auto routines, user definable macros, trig assist and irregular pocket clearing
- Management software that allows editing of large program files at the machine
- MTCconnect compliant
- Networking
- Two USB ports
- Mid-travel with tactile feedback keys

Distributed By: